
Dimensional Information for Genie & Genie Plus





Installation Instructions for Genie & Genie Plus

Important: Turn off all power to the steam generator before control installation.

- 1. Determine the desired location for the control inside the steam room. For optimum function the control should be located:
- 3.5 to 4 feet above the floor
- away from the steam nozzle and not exposed to direct steam emission
- on a vertical wall, preferably near the steam door

The control cable is 30 feet. If additional cable is required contact your supplier or Alladin-Air Mfg. Ltd.

- 2. Drill a one inch hole in the desired control location.
- 3. Route the control cable from the hole to the steam generator.

Important: Do not strain, staple, pinch or otherwise damage the control cable. Route cable as required to permit replacement.

- 4. Locate the control jack on steam generator and insert plug until end "clicks".
- 5. Plug cable into cable coupler (supplied).
- 6. Plug control lead into coupler.

Important: Verify the steam generator is installed according to the instructions and unit has filled with water before turning power on.

- 7. Turn on power to the steam generator and test controller to verify proper control function, as per the operating instructions in the following sections.
- 8. Insure the mounting surface inside the steam room is clean, dry and free of any grease or other contaminants.
- 9. Apply a bead of silicone (supplied) to the back of the control.

Important: Do not apply excessive amounts of silicone. Do not apply silicone to any other part of the control.

- 10. Apply silicone into the hole in the wall as required to create a moisture seal.
- 11. Hold the control with the LED display in the 12 o'clock position and press the control against the wall until the silicone holds firmly.
- 12. Let silicone cure 24 hours before operating the steam room.

Genie Operating Instructions

ON/OFF

Pressing the ON/OFF key will start or stop a steam cycle, and the LED will display the time remaining. Steam will begin to flow a few minutes after the steam bath is turned ON. Steam will continue to flow for a short time after the control is turned OFF. The time duration required for the steam room to reach steam bathing temperature depends on the steam room construction and steam generator specifications

ADJUSTING THE TIME

The control is pre-set and the LED will display a setting of 30 minutes (default setting). Any time the control is turned on, pressing the UP or DOWN keys will adjust the steam bathing duration (maximum 60 minutes) in 1 minute increments. Holding the UP or DOWN key will cause the display to scroll. Set the duration according to personal preference; however it is highly recommended to begin steam bathing at a shorter duration to gauge comfort levels. The steam bath will turn off when the time counts down to zero.

Genie Plus Operating Instructions

ON/OFF

Pressing the ON/OFF key will start or stop a steam cycle, and the LED will display the time remaining. Steam will begin to flow a few minutes after the steam bath is turned ON. Steam will continue to flow for a short time after the control is turned OFF. The time duration required for the steam room to reach steam bathing temperature depends on the steam room construction and steam generator specifications

ADJUSTING THE TIME

The control is pre-set and the LED will display a time setting of 30 minutes (default setting). Any time the control is turned on with the time displayed, pressing the UP or DOWN keys will adjust the steam bathing duration (maximum 60 minutes) in 1 minute increments. Holding the UP or DOWN key will cause the display to scroll. Set the duration according to personal preference; however it is highly recommended to begin steam bathing at a shorter duration to gauge comfort levels. The steam bath will turn off when the time counts down to zero.

USING THE MODE KEY

Any time the control is turned on, the display will show the time remaining in the steam cycle. Pressing the MODE key once will advance the control into temperature mode and the display will show the current temperature inside the steam room. As well, the indicator will light beside the word TEMP. on the display. Pressing the MODE key again will advance the control into temperature adjust mode and the temperature indicator will begin flashing. The control can be operated with either the time remaining or room temperature displayed; however the control will advance back to the TIME mode when 1 minute is remaining. When in the temperature adjust mode, if no keys are depressed for 15 seconds the control will advance to time mode.

ADJUSTING THE TEMPERATURE

With the control advanced into the temperature set mode, the display will show 30 C (default setting). Pressing the UP key will adjust the temperature setting from 30 C to 60 C in one degree increments. Holding the UP or DOWN key will cause the display to scroll. The control is programmed to retain the last temperature setting in memory. When in the temperature adjust mode, if no keys are depressed for 15 seconds the control will advance to time mode. Set the steam bath temperature according to personal preference; however it is highly recommended to begin steam bathing at a lower temperature setting to gauge comfort levels.

Instructions for Care & Cleaning Your Genie or Genie Plus

The finish on your control is not chrome and will scratch as easily as a painted surface. The finish has been protected with a top layer of urethane paint. This top coat is just like the top layer of paint on your vehicle and will scratch or chip just like the painted surface of your car.

We recommend that for the first thirty days you take great care when rubbing or cleaning the chrome surface to avoid swirling marks showing up in the top coat.

Use only a soft non abrasive cloth to clean the surface. Use only mild soap and water and soft cloth to dry and buff the surface. **DO NOT USE** any cleaners containing silicone or ammonia such as vinyl conditioner or window cleaner as over time they will cloud the surface. This is a decorative finish only and we recommend hand washing only.